

## Hinges Full Mortise Hinges - Standard Weight

Full mortise hinge for use on medium weight doors that have medium to high frequency service. They are suitable for hollow metal or wood doors.



### LH1379CB

Certification: ANSI/BHMA A156.1 and A156.7

Description: Standard Weight Concealed bearing 3 knuckle hinges Steel

Sizes:	Inches	mm	Inches	mm
	4-1/2" x 4"	(114X102)	.134	(3.4)
	4-1/2" x 4-1/2"	(114X114)	.134	(3.4)
	5" x 4"	(127X102)	.146	(3.7)
	5" x 4-1/2"	(127X114)	.146	(3.7)
	5" x 5"	(127X127)	.146	(3.7)

Finishes: US26, US26D, US10B

Options: NRP/ETW/PIC/RC

cUL Listing stamp for fire

See page 15-17 for details



### LH1391CB

Certification: ANSI/BHMA A156.1 and A156.7

Description: Standard Weight Concealed bearing 3 knuckle hinges Stainless Steel

Sizes:	Inches	mm	Inches	mm
	4-1/2" x 4"	(114X102)	.134	(3.4)
	4-1/2" x 4-1/2"	(114X114)	.134	(3.4)
	5" x 4"	(127X102)	.146	(3.7)
	5" x 4-1/2"	(127X114)	.146	(3.7)
	5" x 5"	(127X127)	.146	(3.7)

Finishes: US32D

Options: NRP/ETW/PIC/RC/HT

cUL Listing stamp for fire

See page 15-17 for details